

marLED® operating light combination E9i / E9i – ceiling mounting



Mechanical design

Ceiling-mounting operating light consisting of a ceiling tube, a horizontal tracking arm, a spring arm, a cardan joint and a light head. Depending on on-site conditions (ceiling structure), a ceiling anchor plate or an intermediate ceiling assembly is used for mounting the light. With its wide range of action and full adjustability in height, the suspension arm system offers unrestricted movability. Thanks to the use of low-weight materials and an innovative design, the weights and torques involved could be minimized, thus enhancing operator convenience at the same time. The light head features several handles for safe and secure positioning of the light, with a seamlessly integrated membrane keypad offering easy, non-sterile control of all light functions. To meet all hygiene requirements for fast and reliable disinfection, the light comes with a closed housing with patented joining technology, smooth surfaces and smooth form transitions. Due to the design and structure of the laminar flow-optimized light head, the light can be recommended for use under "laminar-flow" ceiling panels.

We reserve the right to make alterations

Light system

High-performance LEDs of different chromaticity are used as a basis for illumination of the surgical site. The special arrangement of the "light engines" inside the light head ensures shadow-free illumination while providing deep-cavity light at the same time. Computer-calculated optical systems boasting a special microstructure enable the color shadow-free illumination of small or large surgical sites. The process of adjusting the light field diameter involves no moving parts at all and is thus entirely maintenance-free. The LED light consists only of visible light without any infrared content. The large number of altogether 36 individual LEDs provides failure safety with an extremely long service life of the light sources.

Operation

All operating functions can be controlled via an ergonomic, flush-integrated membrane keypad. Brightness control and light field adjustment are fully electronic, no mechanical components involved. The currently used setting is indicated via an LED segment display on the control panel. High-precision positioning of the light head in any surgical situation is guaranteed by integrated handle elements that are accessible from all sides.

Optional equipment:

- KLS Martin camera system surgiCam® – for highest demands in terms of image quality and resolution. The system can be optionally installed either in the center of the light head or on a separately available video suspension arm.
- Operating function via sterile handle for sterile control of the size of the light field, the backLite function and the color temperature adjustment.

We reserve the right to make alterations

Electrical Data		marLED® E9i / E9i Ceiling	
Power module incl. mounting plate, dimensions [L x W x H]	mm	200 x 130 x 105	
Power module, primary voltage	V	100 – 240 VAC, 50 – 60 Hz	
Fuses, 24-V side	A	10	10
Fuses, 230-V side	A	5	5
Power input at 220 – 240 VAC	VA	max. 102	
Power input at 100 – 130 VDC	VA	80	
Power input at 24 VDC (small light field, brightness level 8)	W	45	
Power input at camera		8 VA / 5 W	
Voltage at point of wall- or ceiling-mounting	V	24 – 30 VDC	
Effective service life of light sources	h	40,000	
Voltage stabilization (electronic)		yes	yes
Soft-start option (light does not start immediately with full brightness)		yes	yes
Electronic system meets requirements acc. to VDE and IEC		yes	yes
Classification acc. to MPG (Medical Devices Act / MDD)		I	I
Protection class acc. to IEC 601		I	I
Degree of protection: suspension system		IP 30	IP 30
Degree of protection: light head		IP 42	IP 42
Conformity		CE	CE

We reserve the right to make alterations

Photometric Data		marLED® E9i / E9i Ceiling	
Central illuminance, electrically dimmable from / to	%	30 – 100 % / backLite 5 %	
Central illuminance at a distance of 1 m	lx	160,000	160,000
Light field diameter (d10, distance 1 m)	mm	170 – 220	170 – 220
Light field diameter (d50, distance 1 m)	mm	95	95
Color temperature	K	3,600 / 4,300 / 4,600	
Color rendering index [Ra (1 – 8)]		95	95
Red rendering index [R9]		> 85	> 85
Total irradiance at 100,000 lux	W/m ²	293	293
Total irradiance at 160,000 lux	W/m ²	469	469
Luminous efficacy	lm/W	320	320
Illumination depth (20 % on E _C max. without refocusing) L1/L2	mm	330 / 430	330 / 430
Illumination depth (60 % on E _C max. without refocusing) L1/L2	mm	180 / 200	180 / 200
Working range from/to (20 % on E _C max. without refocusing)	mm	670 – 1,430	670 – 1,430
Working range from/to (60 % on E _C max. without refocusing)	mm	820 – 1,200	820 – 1,200
Shadow dilution with one mask	%	63	63
Shadow dilution with two masks	%	48	48
Shadow dilution with one tube	%	99	99
Shadow dilution with one tube and one mask	%	50	50
Shadow dilution with one tube and two masks	%	45	45
UV irradiance for wavelengths < 400 nm	W/m ²	< 10	< 10

We reserve the right to make alterations


Mechanical Data		marLED® E9i / E9i Ceiling	
Min. room height (power module on ceiling flange 2.25 m)	mm	2,980	
Min. room height (external power module / headroom 2.25 m)	mm	2,840	
Operating forces on light head	N	acc. to norm	acc. to norm
Range of movement	mm	1,760	1,760
Spring arm height adjustment (depending on room height)	mm	1,178	1,178
Top position of light head at a headroom of 2.25 m	mm	2,288	2,288
Dimensions: diameter of ceiling anchor plate	mm	380 (square)	
Bottom position of light head at a headroom of 2.25 m	mm	1,110	1,110
Force required for moving light head up/down	N	14	14
Force required for swiveling the light head	N	6	6
Max. vertical force due to weight	N	approx. 450	approx. 450
Total weight	kg	39	39
Single weight (approx.): standard ceiling tube	kg	8	
Single weight (approx.): tracking arm, central bearing shaft, spring arm	kg	12	12
Single weight (approx.): power module	kg	7	7
Single weight (approx.): light head	kg	12	12
Torque, bending moment	Nm	approx. 290	approx. 290
Permissible ambient temperature range during operation	°C	5° to +40° C	
Storage temperature	°C	-10° to +50° C	
Shock/impact resistance		8 g / 10 ms	
Vibrostability (immunity to vibration)		10 – 150 Hz / 0.15 mm / 2 g	
Canopy dimensions	mm	620 x 208 (110)	
Light head flow contact area	cm ²	2,775	2,775
Light head height (w/o sterile handle)	mm	70	70
Light head dimensions	mm	685 x 630	685 x 630

Manufacturer: Gebrüder Martin GmbH & Co. KG

Type: marLED® E9i / E9i Ceiling

We reserve the right to make alterations

Technical drawing



We reserve the right to make alterations